



BELT DRESSING

LPS® Belt Dressing is formulated to extend belt life, prevent belt slippage, and resist water wash out.



*Visit www.lpslabs.com/LPS_icons.html for more information

PACKAGE SIZE

Net Contents	Part No.
10 wt. oz. / 284 g / 445 mL	02216

APPLICATIONS

- Appliance Drive Belts
- Bearings
- Bushings
- Flat Belts
- Polishing Belts
- Round Belts
- Sanding Belts
- Toothed Belts
- V-Belts

PROPERTIES

Appearance/Physical State: Clear/ colorless liquid	HMIS: 1, 3, 0	Temperature Range: 32°F (0°C) to 325°F (163°C)
Auto Ignition Temperature: 788°F (420°C)	Propellant: Propane/Isobutane Blend	Vapor Pressure: 352 mmHg @ 100°F (38°C)
Coverage: 34 ft ² /can @ 5 wet mils 17 ft ² /can @ 10 wet mils	Spray Pattern: Mist	VOC: 90% per State & Federal Consumer Product Regulations 597 g/L per SCAQMD Rule 102
Evaporation Rate: <1 (Ethyl Ether=1)	Specific Gravity (water=1): 0.67 - 0.69 @ 68°F (20°C)	

DIRECTIONS

Shake well before using. Turn off equipment and stop belts before applying. Spray inner surface of belt from a distance of 6 to 8 inches. Use only enough to cover belt. Let vapors dissipate. If desired, attach extension tube for difficult to reach areas. Repeat as needed. Avoid contamination of food in the application and storage of the product. Do not add directly to food. Use only in well ventilated areas. Avoid all sources of ignition (spark or flame).

DISPOSAL INFORMATION

Waste must be disposed of in accordance with national, regional, provincial, and local environmental control regulations.

FEATURES

- Prevents belt slippage on flat, round, and V-belts
- Eliminates squeaks from slipping belts
- Water resistant
- Extends belt life and pulley bearing life
- Does not contain chlorinated solvents that deteriorate drive belts
- Metal detectable plastic components (see back for more details)
- May be used in wet, outdoor conditions
- NSF® Certified: H1 Registration # 134508

SPECIFICATIONS AND APPROVALS

- Meets FDA Regulation 21 C.F.R. 178.3570 for incidental food contact
- NSF® Certified: H1 Registration # 134508
- Acceptable for use in Canadian food processing establishments

STORAGE

Keep container closed and in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F. Store aerosols as Level 3 Aerosol (NFPA 30B). Product is stable under recommended storage conditions. Keep away from heat and ignition sources. Do not expose to direct sunlight for extended periods.

CLEAN-UP

Turn can upside-down and spray to clear nozzle.



METAL DETECTABLE PLASTIC COMPONENTS

(PATENT PENDING)



Scan to watch Detex™ Product Demo Video

Universal blue color for all Metal Detectable plastic components easily identifies them as a non-food object

Cap

Actuator

Extension Tube

Alignment dot

Highly visible NSF® H1 labeling

Premium quality product

Certified food safe container

Dual language labeling: English and Spanish

2-piece aerosol can; 10% – 15% lighter than a 3-piece aerosol can



LPS® Detex™ Metal Detectable Plastic Components are designed to assist food processing plants in meeting strict HACCP requirements regarding the use of LPS® NSF® H1 aerosol products in the food processing area.

FEATURES	BENEFITS
All plastic components are Metal Detectable and capable of detection by most metal detection equipment.	Reduce concerns of food product contamination and assist with HACCP requirements.
All Metal Detectable plastic component ingredients are GRAS listed (Generally Accepted As Safe - 21 C.F.R. Sections 177 and 178).	Meets FDA requirements as an acceptable material for use in food processing plants.
Easily identified NSF® H1 product labeling. NSF® H1 lubricants can have incidental food contact.	Distinct Food Grade product labeling helps to prevent use of non NSF® H1 approved LPS® products in the food processing area.
Lithographed labels – LPS® does not use paper labels.	No chance of torn paper labels contaminating food as it is processed.
Aerosol can is in compliance with the The Food Safety Net Services (FSNS). FDA 21 C.F.R. 175.300, 1935/2004/EC.	Aerosol can does not contain: Heavy metals, BADGE, BFDGE, NOGE and Bisphenol-A (BPA).

- NOTE:**
- Minimum detection limits will vary depending on individual customers' equipment and operating conditions. (See chart below)
 - Plastic component detection limits are based on whole components. Partial components may not be detectable due to detector limitations, partial component size, malfunctioning equipment and/or the type of food product undergoing processing.
 - LPS® Laboratories recommends that all components be tested prior to implementation (separately and included in the processed food product) and/or consult your specific metal detector equipment manufacturer directly.
 - Product shelf life, warranty, and material safety data sheets are available at www.lpslabs.com. LPS® Laboratories is not responsible for use of this product inconsistent with its instructions and warnings.
 - LPS® Laboratories is not responsible for failure to detect components due to detector limitations and/or detector malfunctions. Refer to the metal detector manufacturer's design limitations, instructions, and warnings regarding the use, limitations, and proper maintenance of the equipment.

COMPONENT	EQUIVALENT TEST SPHERE SIZE
Aerosol Cap	>3.0 mm Ferrous
Actuator	2.2 mm Ferrous
Extension Tube	1.0 mm Ferrous



SAFETY DATA SHEET

LPS Belt Dressing Aerosol Spray Can

Revision 6

Revision Date 29/5/07

Supercedes: 30/3/07

Section 1 – Identity of the Substance/Preparation and Company/Undertaking

Product Name: LPS BELT DRESSING (AEROSOL SPRAY CAN)

Part Numbers: M22400

Product Use: A spray product degreaser designed for removing heavy residues from metal and other hard surfaces where reduced flammability, toxicity and environmental impact are concerns.

Supplier: Geocel Limited, Western Wood Way, Langage Science Park, Plympton, Plymouth, PL7 5BG United Kingdom

TEL: +44 (0)1752 202060

FAX: +44 (0)1752 334384

In Case of Emergency: +001 703-527-3887

Manufacturer: LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA 30085 (U.S.A.)
<http://www.lpslabs.com>

Section 2 – Hazards identification

Human and Environmental Hazards This preparation is considered hazardous according to European Union Directives 67/548/EEC and 1999/45/EC. This product will combust when subjected to ignition sources. Do not spray on a naked flame or any incandescent material.

Extremely flammable. Irritating to skin. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Remark: The classification for aspiration hazards (R65), does not apply for products placed on the market in aerosol containers. (EU-Directive 67/548 Annex VI 9.4). Inhalation of concentrated petroleum distillate mist or vapours can cause central nervous system (CNS) depression.

Section 3 – Composition / Information on Ingredients

INGREDIENT NAME	EC No.	CASRN	Classification	Weight Percent
2-methylpentane	203-523-4	107-83-5	[F] R11; [Xi] R38; [N] R50/53; [Xn] R65; [-] R67	50 - 70 %
Hydrocarbon Aerosol Propellant*	270-704-2	68476-85-7	[F+] R12; [T] R45, R46	15 - 30 %

*This component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note K in Annex I of 67/548/EEC, and is exempt from a classification of T; R45, R46. (Contains less than 0.1% 1,3 butadiene) See "Section 11: Toxicological Information" for information regarding the classification of substances.



SAFETY DATA SHEET

LPS Belt Dressing Aerosol Spray Can

Revision 6

Revision Date 29/5/07

Supercedes: 30/3/07

Section 4 – First Aid Measures

- Eyes:** Liquid contact may cause irritation. Flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention if irritation persists.
- Skin:** Get medical attention if irritation persists.
- Inhalation:** If inhaled, remove to fresh air. If breathing is difficult, give oxygen and get medical attention. If not breathing, give artificial respiration and get medical attention.
- Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention immediately.

Section 5 – Fire Fighting Measures

- Rate of Burning:** Not Available. **Products of Combustion:** carbon monoxide and carbon dioxide.
- General Fire Hazards:** While this material is not considered flammable, high heat will cause product to boil, evolving vapour that could cause explosive rupture of closed containers.
- Firefighting media:** SMALL FIRE: Use DRY chemical powder.
LARGE FIRE: Use water spray, fog or foam. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosions.
- Sensitivity to Impact:** None. **Sensitivity to Static Discharge:** See sections 6,7,8 and 15.
- Protection Clothing (Fire):** wear protective clothing and equipment suitable for the surrounding fire, including helmet, face mask, and self-contained breathing apparatus.

Section 6 – Accidental Release Measures

- Precautions to protect environment:** Do not allow entry into drains or watercourses. If this occurs inform the local authorities at once.
- Spill Cleanup methods:** This product is a hermetically sealed pressurised aerosol unit and accidental spillage is unlikely. If can is ruptured, allow contents to discharge in situ, whilst removing all ignition sources from the area and ensuring maximum ventilation. Use an absorbent material, eg sand, to mop up residues. See section 13 'Disposal Considerations'.

Section 7 – Handling and Storage

- Usage Precautions:** Do not spray on a naked flame or any incandescent material.
- Storage Precautions:** Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. It is recommended that aerosols are stored in their own location away from bulk flammable liquids and packaging materials. Store in a cool, dry place away from heat and ignition sources.



SAFETY DATA SHEET

LPS Belt Dressing Aerosol Spray Can

Revision 6

Revision Date 29/5/07

Supercedes: 30/3/07

Section 8 – Exposure Controls / Personal Protection

Component	EC No.	UK LT EXP (8 hrs.)	UK ST EXP (15 min.)	Other
2-methylpentane	203-523-4	200 ppm	Not Established	500 ppm ACGIH-TLV 1000 ppm ACGIH-STEL
Hydrocarbon Aerosol Propellant	270-704-2	1000ppm 1750mg/m ³	1250ppm, 2180mg/m ³	1000 ppm ACGIH-TLV

Engineering measures Normal room ventilation is usually adequate. If necessary, use appropriate local exhaust ventilation to keep exposures below the regulated limits.

Personal protective equipment

Eye protection Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and emergency shower facilities are recommended.

Hand protection Normally no hand protection is required; however, if product will be sprayed for an extended period, "overspray" onto skin may occur. If so, use protective gloves conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves. Take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion and the contact time.

Respiratory protection Typical use of this product under normal conditions does not require the use of respiratory protection. If extended spraying of product will be made under poor ventilation, use appropriate organic vapor filtering respirators.

Hygiene measures Do not soak clothing with this product and continue working without immediately changing clothes and washing skin. Do not reuse clothing until it has been laundered. An eyewash fountain should be available in the work area.

Environmental exposure controls Soak up puddles of product (from a crushed or ruptured aerosol) with absorbent material and dispose of according to local regulations. Ventilate area to reduce worker exposure to vapours and prevent accumulation of explosive vapour concentrations.

Section 9 – Physical and Chemical Properties

Appearance:	Liquid.	Colour:	Colourless.
Odour/Taste:	Characteristic.	Vapour Pressure:	47 kPa @ 20 °C
Solubility Description:	Not soluble in water.	Evaporation Rate:	<1.0(ethyl ether=1)
Boiling Point (°C):	61 @ 101mmHg	Flash Point (°C):	<-11°C
Specific Gravity (Water=1):	0.67 – 0.69 @ 20 °C	Flash Point Method:	Tag-Closed Cup.
Vapour Density (air=1):	3.0	Auto Ignition Temperature (°C):	420°C
V.O.C. Content:	646 g/L	Partition Coefficient (octanol/water):	3.2
Flammable limits (estimated):	LOWER: 1% UPPER: 6%	pH:	Not applicable



SAFETY DATA SHEET

LPS Belt Dressing Aerosol Spray Can

Revision 6

Revision Date 29/5/07

Supercedes: 30/3/07

Section 10 – Chemical Stability and Reactivity

Chemical Stability:	Product is stable under recommended storage conditions.
Conditions to Avoid:	Exposure to direct sunlight for extended periods. Temperatures in excess of 50°C.
Incompatibility:	Reactive or incompatible with oxidizing agents.
Hazardous Decomposition:	Combustion will generate smoke, possibly thick and choking, resulting in zero visibility and combustion products include carbon monoxide and carbon dioxide.
Hazardous Polymerization:	Will not occur.

Section 11 – Toxicological Information

Acute and Chronic Toxicity

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

B: Component Analysis

Ingredients	EC No.	LC-50	LD-50
2-methylpentane	203-523-4	3125 ppm/4 hrs./rat	Not available.
Hydrocarbon Aerosol Propellant	270-704-2	Not available.	Not available.

Note, the 270-704-2 component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note K in Annex I of 67/548/EEC, and is exempt from a classification of T; R45, R46. (Contains less than 0.1% 1,3 butadiene)

Section 12 – Ecological Information

Mobility:	Semi-volatile. Readily absorbed into soil.	Persistence and degradability:	Only slightly biodegradable.
Bioaccumulative potential:	No bioaccumulation potential	Other adverse effects:	None known.

Component Information

Acute Aquatic Toxicity

Component	CASRN	Test	Species	Results
2-methylpentane	107-83-5	48-hour EC ₅₀	Daphnia magna	2.1 mg/L
		96-hour EC ₅₀	Microcystis pyrifera	10 mg/L
Hydrocarbon Aerosol Propellant	68476-85-7	48-hour EC ₅₀	Daphnia magna	Not available
		96-hour EC ₅₀	Microcystis pyrifera	Not available



SAFETY DATA SHEET

LPS Belt Dressing Aerosol Spray Can

Revision 6

Revision Date 29/5/07

Supercedes: 30/3/07

Section 13 – Disposal Considerations

Disposal: Waste must be disposed of in accordance with national and local environmental control regulations.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate.

Section 14 – Transportation Information

ADR/RID	UN No.	1950	ADR Class:	2
	Classification code:	5F	Shipping name:	AEROSOLS, flammable
	Labeling:	2.1		
IMDG-IMO	UN No.	1950	Class:	2
	EmS:	F-D,S-U	Labeling:	NA
	Shipping Name:	AEROSOLS		
IATA-ICAO:	UN no:	1950	Class:	2.1
	Shipping Name:	Aerosols, flammable	Labeling:	Flammable Gas

Section 15 – Regulatory Information

Warning Symbol(s):	F+, Xi, N
Risk Phrases:	R-12 Extremely Flammable R-38 Irritating to skin R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-67 Vapours may cause drowsiness and dizziness.
Safety Phrases:	S-2 Keep out of the reach of children. S-16 Keep away from sources of ignition – No Smoking S-29 Do not empty into drains. S-33 Take precautionary measures against static discharges. S 60 This material and its container must be disposed of as hazardous waste. S 61 Avoid release to the environment. Refer to special instructions/safety data sheets.
Precautionary Phrases:	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Section 16 – Other Information

User Notes: The purpose of the above information is to describe this product only in terms of Health and Safety requirements. The information given therefore, should not be construed as guaranteeing specific properties or specification. Customers should satisfy themselves as to the suitability and completeness of this information for their own particular use, bearing in mind any other Health and Safety legislation or regulations. The information and recommendations in this publication are to the best of our knowledge reliable. However, nothing herein is construed as a warranty or representation. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.



SAFETY DATA SHEET

LPS Belt Dressing Aerosol Spray Can

Revision 6

Revision Date 29/5/07

Supercedes: 30/3/07

Information Sources:

ESIS: European Chemical Substances Information
HSE EH40 Occupation Exposure Limits. Suppliers Safety Data Sheets.

Full R-Phrases

R-11	Highly Flammable
R-12	Extremely Flammable
R-38	Irritating to skin
R 45	May cause cancer
R 46	May cause heritable genetic damage
R-50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R-65	Harmful: may cause lung damage if swallowed.
R-67	Vapours may cause drowsiness and dizziness.